

Ramp Function v6 RAF185

DESCRIPTION

The RAF185 is for applications requiring process signal ramping and pulse accumulation. Such applications include motor start-up and speed control or applications requiring time base manipulation. Ramping options include up, down or up/down and stair case control of process signal outputs over an adjustable time base. Pulse accumulation options include up, down or up/down step control of process signal outputs. All timing and accumulation tasks are performed by a microprocessor. Inputs available included voltage free contacts or external source pulses. Inputs are indicated by 3mm green LED to verify proper input wiring. Time base (Period) adjustments are adjustable via front accessible 15-turn trim potentiometers. Final calibration is trimmed using the front accessible 'offs' and 'span' 15-turn trim adjustments.



General Specifications

Size:	52 W x 70 H x 110 D (mm).
Mounting:	DIN-Rail, gear plate.
Termination:	Screw terminals on front.
Weight:	0.300 kg.
Housing material:	ABS.
Protection class:	IP40.
Calibration accuracy:	<0.2% of range.
Temperature effect:	<0.02% per °C.
Ambient operating range:	-10...+60°C.
Storage temperature range:	-20...+70°C.
Combined linearity/drift error:	<0.2% of span.
Power requirements:	3W.
Power supply isolation:	2kVrms.
Electromagnetic compatibility:	Complies with AS/NZS 4251.1 (EN 50081.1)
Ramp time minimum:	0.2 seconds.
Ramp time maximum:	400 seconds.


Process Signal Output Version

Output loop drive:	20mA into 0 – 900Ω.
Output load change effect:	less than 0.2% up to max load.
Front 'OFFS' adjust:	±5% typical
Front 'SPAN' adjust:	±5% typical


PWM Output Version

Voltage free contact output:	50V/100mA max (FET).
PWM current /voltage pulse:	5mA constant current drive (20V unloaded, use a load resistor to set voltage).
PWM frequency range	20Hz (50mS) to 1kHz (1mS)

Process Output Version




PWM Output Version




Operating Modes


Standard Ramp (Opt 0)



Stair Case Generator (Op 2)



Up/Down Counter (Opt 3)



Output goes low if reset detected regardless of other input

TYPE NO. DESIGNATION

Power Supply:

- 1 = 90-280Vac 50/60Hz (65-280Vdc).
- *) 3 = 16-48Vac 50/60Hz (10-60Vdc)
- 6 = 8 - 60Vdc.

Input 1 (Up):

- 0 = None.
- 1 = 24Vdc pulse external source (0.2 – 50Vdc)
- 2 = Contact.
- 3 = NPN open collector
- 4 = PNP open collector
- *) 9 = Other specify.

Input 2 (Down):

- 0 = None.
- 1 = 24Vdc pulse external source (0.2 – 50Vdc)
- 2 = Contact.
- 3 = NPN open collector
- 4 = PNP open collector
- *) 9 = Other specify.

Output:

- 1 = 0 - 5V (50kΩ min).
- 2 = 0 - 10V (100kΩ min).
- 3 = 0 - 20mA (900Ω max).
- 4 = 4 - 20mA (900Ω max).
- 7 = 0 - 10mA (1.8kΩ max).
- 8 = 1 - 5V (50kΩ min).
- *) 9 = Other process signal specify.
- A = PWM voltage free contact
- B = PWM 5mA CC drive pulse.
- Specify PWM frequency and %min/max duty cycle.

Period (Up):


Period (Down):

- 1 = 0.2 - 5 sec adjustable.
- 2 = 0.2 - 10 sec adjustable.
- 3 = 0.2 - 30 sec adjustable.
- 4 = 0.2 - 60 sec adjustable.
- *) 9 = Specify specify 400 seconds max

Options:

- 0 = Standard ramp function.
On "Input 1" output will rise at the period up rate. On "Input 2", output will fall at the period down rate. Output steady for no input.
- *) 1 = External adjustments.
Same functional description as standard except one or both "Period Up" and "Period Down" controls (pots) are wired via 1.5m cable for external mounting.
- *) 2 = Stair case generator.
Specify number of steps. Input 1 = start.
- *) 3 = Up down counter.
Specify number of steps for full scale between 16 and 1024.
Each "Input 1" pulse will increment the output by 1/(steps) of full scale. Each "Input 2" pulse will decrement the output by 1/(steps) of full scale.
- *) 4 = Quad input pulse accumulator.
Pulses on inputs 1 to 4 are reproduced at the output. The internal circuits will compensate for overlapping inputs.
- *) 5 = Position, quadrature input with analogue output. Specify number of steps for full scale between 128 and 1152. The phase difference between "Input 1" and input 2 will determine if the output should increment or decrement the output by 1/(steps) of full scale.
- *) 9 = Other (Specify).

Ramp Connection



*) = Price Extra.

In the interest of development and improvement, APCS reserve the right to amend, without notice, details contained in this publication. APCS will accept no legal liability for any errors, omissions or amendments.